

03/30/99



JC645 U.S. PTO

A

Docket Number E-831
 Pitney Bowes Inc.
 35 Waterview Drive
 P.O. Box 3000
 Shelton, CT 06484-8000
 March 30, 1999

BOX PATENT APPLICATION
 ASSISTANT COMMISSIONER FOR PATENTS
 WASHINGTON, D.C. 20231

JC640 U.S. PTO
 09/280528

 03/30/99

Sir:

Transmitted herewith for filing is the patent application of

Inventor: Robert A. Cordery, et al.

For: METHOD FOR CERTIFYING PUBLIC KEYS USE TO SIGN POSTAL INDICIA AND INDICIA SO SIGNED

Enclosed are:

Thirty-two (32) pages comprising the specification, claims, and abstract.

Nine (9) sheets of drawing.

A Declaration and Power of Attorney.

Fees calculated as follows:

Basic Fee							\$ 760.00
Claims Fee	Number Filed		Number Extra		Rate		
Total Claims	13	- 20 =	0	X	\$18.00	=	\$ 0.00
Independent Claims	6	- 3 =	3	X	\$78.00	=	\$ 234.00
Multiple Dependent Claims					\$260.00	=	\$
Total Filing Fee							\$ 994.00

Please charge our Deposit Account Number **16-1885** in the amount of \$ 994.00 for the filing fee.

The Commissioner is hereby authorized to charge any additional fees which may be required, or credit any overpayment to Account Number **16-1885**.

A copy of this Transmittal Letter is enclosed for use in charging the Deposit Account.

Charles R. Malandra, Jr.
 Reg. No. 31,038
 Attorney of Record
 Telephone (203) 924-3217

03/30/99

**METHOD FOR CERTIFYING PUBLIC KEYS USED TO SIGN POSTAL
INDICIA AND INDICIA SO SIGNED**

Related Applications

The present application is related to, and discloses subject matter common to
5 commonly assigned, co-pending applications serial numbers: _____ ,
_____ (att. docket E-837, E-838) filed on even date herewith.

Background of the Invention

The subject invention relates to encryption of information using public key
encryption technology. (By "public key" encryption herein is meant encryption
10 technology which uses pairs of keys: a public key, which is published or made publicly
known; and a corresponding private key, kept secret by a user.) More particularly it
relates to the use of private keys to certify postal indicia and the like and the certification
of corresponding public keys.

15 Using public key encryption anyone can encrypt a message with a public key and
have assurance that only a user (i.e. a party having the corresponding private key) can
decrypt it, and a user can "sign" a message using the corresponding private key and
anyone can use the public key to ascertain if the message originated with the user. (A
message is "signed" by encrypting information derived in a known manner from the
20 message.)

Because public keys can be distributed so widely, it will in general be the case that
persons communicating with users of public key systems will not be in direct contact with
the users and will not be able to directly determine the identity and/or characteristics of

the putative users of a public key system. For example, proof of payment systems, in particular postage meters, which generate indicia encrypted using public key systems as proof of payment have recently been developed by the assignee of the present application and others; and, given the hundreds of thousands of postage meters in service, it is clear
5 that the postal services will face a severe problem in assuring that indicia purportedly generated by a meter corresponding to a particular public key is in fact generated by an authorized postage meter.

To overcome the difficulties inherent in authenticating public keys numerous
10 schemes for issuing certificates for public keys have been proposed. In such schemes, a trusted third party (hereinafter sometimes a “certifying authority”) provides parties who wish to communicate with a user with a certificate containing the user’s public key, the certificate serving to evidence the third party’s assurances as to the identity or characteristics of the user. In the simplest case such certificates are no more than entries
15 in a directory delivered through a secure channel. More generally the certifying authority will use an encryption technology to deliver the certificate.

In U.S. patent no.: 4,853,961; for: “Reliable Document Authentication System”;
to: Pastor, a public key for a postage meter is encrypted with a third party’s private key
20 and included in the meter indicia. The postal service uses the third party’s public key to recover the meter public key and decrypt the encrypted message which serves to validate the indicia.

In U.S. patent no.: 5,661,803; for: “Method of Token Verification in a Key
25 Management System”; to: Cordery et al., a method of token verification in a key management system is disclosed.

In U.S. patent no.: 5,680,456; for: “Method of Manufacturing Generic Meters in a
Key Management System”; to: Baker et al., a method for manufacturing transaction
30 evidencing devices such as postage meters includes the steps of generating a master key

in a logical security domain of a key management system and installing the master key in a postage meter.

In U.S. patent no.: 5,742,682; for: "Method of Manufacturing Secure Boxes in a Key Management System"; to: Baker et al., a method of manufacturing a secure box in a key management system is taught.

In U.S. patent no.: 5,805,701; for: "Enhanced Encryption Control System for a Mail Processing System Having Data Center Verification"; to: Ryan, Jr., a key control system comprising generation of a first set of master keys and assigning the keys to a corresponding plurality of postage meters is taught.

In U.S. application serial no.: 08/133,416; by: Kim et al.; filed Oct. 8, 1993, a key control system comprising generation of a first set of master keys and assigning the keys to a corresponding plurality of postage meters is taught. Keys may be changed by entry of a second key via encryption with a first key.

In U.S. application serial no.: 08/772,739; by: Cordery; filed Dec. 23, 1996, a method for controlling keys used in the verification of encoded information generated by a transaction evidencing device and printed on a document is taught.

The ITU X509.3 standard teaches a standard in which a first user's certificates includes the user's public key, identification and authorization information, and a signature of the certificate authority. A second user verifies a signature of a message generated by the first user by verifying that the authorization information is satisfactory, that the certificate authority's signature on the certificate verifies, extracting the first user's public key, and verifying the signature.

While the above methods are successful in achieving their intended purpose they are disadvantageous in that they are computationally complex, may produce certificates which are large and inflexible, and may require special hardware.

5 The following references contain information useful to a general understanding of elliptic curve encryption and certification of public keys.

Secure Hash Standard – FIPS PUB 180-1," April 17, 1995.

10 Digital Signature Standard – FIPS PUB 186," May 19, 1994 and Change 1,
December 30, 1996.

ANSI X9.62, Elliptic Curve Digital Signature Algorithm Standard (ECDSA),
15 Working Draft, January 15, 1997.

ISO/IEC 9594-8 (1995). Information Technology – Open Systems Interconnection
– The Directory: Authentication Framework."

20 PKCS #10: Certification Request Syntax Standard, An RSA Laboratories
Technical Note," Version 1.0, December 1993.

Another method of key certification based upon elliptic curve public key encryption technology has been developed by the Certicom Corporation. (The use of
25 elliptic curve encryption technology is known and a more detailed description of its use, beyond what is given below in the context of certification of public keys, is not required for an understanding of the subject invention.)

Elliptic curve encryption is an example of a cryptographic algorithm based on
30 application of an binary operator to points in a finite group. In elliptic curve encryption a

finite group of points $[P]$ of order n is defined on an elliptic curve. A binary additive operator $[+]$ (hereinafter sometimes “point addition”) is defined on the group $[P]$ such that $P [+]$ P' is a point in $[P]$. A more detailed, graphical description of point addition is shown in Figure 1. As is known to those skilled in the cryptographic art, disjoint curve 10 has the general form $y^2 = x^3 + ax + b$ defined over the finite Galois field $GF(p^m)$ where p is a prime number other than 2 and m is an integer. Over the Galois field $GF(2^m)$ the curve has the form $y^2 + xy = x^3 + ax + b$. It can be shown that groups of discrete points $[P]$ of order n can be defined on curve 10, where n is preferably a number on the order of at least 50 decimal digits in order to provide sufficient security for encrypted information.

As is seen in Figure 1 curve 10 is symmetric about the x axis so that for any point (x,y) on curve 10 its reflection around the x axis $R(x,y) = (x,-y)$ is also on curve 10.

For two points P, P' in $[P]$ it can be show that there exists a unique point $R(P [+]$ $P')$ which is a third point common to straight line 12 defined by P and P' and curve 10. $P [+]$ P' is defined as $R(R(P [+]$ $P'))$.

Figure 2 shows the special case for computation of $P [+]$ P . Straight line 14 is defined as tangent to the closed portion of curve 10 and intersecting point P , and $R(P [+]$ $P)$ is defined as the second point common to line 14 and curve 10.

A second operation $K*P$ (herein after sometimes “point multiplication”) is defined as the application of $[+]$ to K copies of a point P . Figure 3 geometrically illustrates computation of $5*P$ by successive computation of the points $P [+]$ $P = 2*P$, $2*P [+]$ $2*P = 4*P$, $4*P [+]$ $P = 5*P$. Point multiplication is the basic operation underlying elliptic curve encryption and has the property that computation of K from knowledge of the group $[P]$, a particular point P , and $K*P$ is hard.

By “hard” as used herein in regard to computation is meant a computation wherein the time required increases faster than the order of the operands $\log n$, preferably

exponentially or faster with the order of the operands $(\log n)^x$; where $x < 1$. This means that where K is of order n , the order of $[P]$, and n is chosen large enough the cost, in time or money, of computing K from knowledge of the definition of $[P]$, P , and $K*P$ can be made arbitrarily large while the cost of other computations relating to encryption or decryption remains relatively low and practicable. Of course those skilled in the encryption art will recognize that, even though encryption and decryption can in principle be carried out by manual computation, the possibly of an attack on an encryption scheme using modern computer technology requires that, in practice, the order n be so great that even the relatively easy computations must be carried out by automated encryption stations; e.g. special purpose, or specially programmed general purpose, digital processing systems.

Point multiplication has been described in terms of the group represented by point addition on a discrete elliptic curve. In other embodiments the subject invention can be implemented using any group representation where determining K is hard given the point P and the point formed by combining K copies of point P by repeated application of the group additive point operation .

In elliptic curve encryption a user U has a private key Key_U and a corresponding public key Key_U*P ; where P is a published or publicly known point in $[P]$. To generate a certified public key in accordance with the above mentioned Certicom encryption scheme user U (i.e. a station operated by user U) generates and keeps secret a random number r_U ; and computes and sends to a certifying authority CA the point r_U*P . Certifying authority CA has a private Key_{CA} and a public key $Key_{CA} *P$. Upon receipt of r_U*P the CA generates a random number r_{CA} and computes and publishes a certificate including a point, $r_U*P [+]$ $r_{CA}*P$, wherein r_{CA} is a random number generated by the CA (i.e. by the CA station). Authority CA , which is presumed to have the capability to directly determine the identity or characteristics of user U , also generates information ID_U and about U includes ID_U in the certificate. Certifying Authority CA then returns an integer derived from the CA 's private key and the certificate to the user station which uses that integer to

compute key Key_U in such a manner that a party communicating with user U can compute $Key_U * P$ from the certificate and the certifying authority's public key Key_{CA} , providing evidence that the certifying authority has linked user U , Key_U , and ID_U .

5 The above described certification scheme is believed to be advantageous in that it is computationally simpler, produces smaller certificates, and does not require special secure hardware. However it does not address the special situation of certification of public keys used to verify value evidencing indicia such as digital postal indicia. For example, a Postal Service which wishes to verify encrypted metered mail may need
10 assurance that the putative public key of a meter has been certified by the meter manufacturer or one or more agencies of the Postal Service. It is also desirable that digital signatures (hereinafter sometimes Cryptographic Integrity Validation Code or CIVC) of postal indicia and the like satisfy the following requirements:

15 1. The CIVC must possess cryptanalytic strength above a predetermined threshold, typically 2^{80} operations; that is the best known algorithms the find a secret key from publicly available plain texts and cyphertexts requires at least 2^{80} operations.

20 2. The CIVC should be of minimal size due to limitations of space available for postal indicia and the like, and the CIVC size needed to maintain required cryptanalytic strength should increase slowly with improvements in cryptanalytic algorithms.

25 3. Computational requirements to generate and verify CIVC's should be compatible with the fastest mail generation or verification equipment.

 4. The indicia, including CIVC's, should contain all the information needed for verification.

30 5. The indicia should contain information allowing the verifier to perform audit functions to reduce risk of misuse of carrier funds. In particular certification of a postage

meter key should also implicitly evidence meter operating parameters such as expiration date or maximum postage value.

6. Costs of the system, including infrastructure such as key management systems, should be minimal.

Methods and systems based on known public key cryptographic schemes such as RSA, DSA, or ECDSA have been suggested but are not believed to fully satisfy the requirements of a digital postage metering system. Accordingly it is an object of the subject invention to provide a method for controlling, and distributing information among, digital postage meters, and the like, and a certifying authority so that such meters can generate indicia, and public keys for verifying such indicia can be certified in a functionally satisfactory and cost effective system.

Brief Summary of the Invention

The above object is achieved and the disadvantages of the prior art are overcome in accordance with subject invention by method for controlling a digital postage meter and a certifying station operated by a certifying authority CA for publishing information, so that a public key $\text{Key}_{\text{DM}} * P$ of the digital postage meter can be determined by a party seeking to verify indicia printed by the digital postage meter from the published information with assurance that the public key $\text{Key}_{\text{DM}} * P$ has been certified by the certifying authority CA, where the method includes; defining and publishing a finite group $[P]$ with a binary operation $[+]$ and publishing a particular point P in the group; defining and publishing a binary operation $K * P$, where K is an integer and P is a point in the group, such that $K * P$ is a point in the group computed by applying the operation $[+]$ to K copies of the point P , and computation of K from knowledge of the definition of the group $[P]$, the point P , and $K * P$ is hard. The certifying station is controlled to publish a certificate CERT_{DM} for the digital postage meter, wherein;

$CERT_{DM} = (r_{DM} + r_{CA}) * P$; and wherein

r_{DM} is a random integer generated by the digital postage meter and r_{CA} is a random integer generated by the certifying station;

and to publish a message M ; generate an integer I_{DM} ; and send the integer to the digital postage meter, wherein;

$I_{DM} = r_{CA} + H(M)Key_{CA}$; and wherein

$H(M)$ is an integer derived from the message M in accordance with a publicly known algorithm H and Key_{CA} is a private key of the certifying authority CA . A public key $Key_{CA} * P$ for the certifying authority CA is published; and the digital postage meter to computes a private key Key_{DM} :

$Key_{DM} = r_{DM} + I_{DM} = r_{DM} + r_{CA} + H(M)Key_{CA}$.

The digital postage meter then prints an indicium and digitally sign the indicium with the key Key_{DM} . A verifying party can then compute meter public key $Key_{DM} * P$ as

$Key_{DM} * P = CERT_{DM} + H(M) Key_{CA} * P =$

$(r_{DM} + r_{CA}) * P + H(M)Key_{CA} * P$

from knowledge of H , M , $[P]$, the public key $Key_{CA} * P$, and $CERT_{DM}$.

In accordance with one aspect of the subject invention the publicly known manner for deriving an integer from the published information includes applying a hashing function to the message M .

In accordance with another aspect of the subject invention the message M includes information IAV identifying the digital postage meter and operating parameters applicable to the digital postage meter.

In accordance with another aspect of the subject invention the group $[P]$ is defined on an elliptic curve.

In accordance with another aspect of the subject invention the message M includes information tying the user's public key $Key_U * P$ to the information IAV .

An article in accordance with the subject invention has an indicium imprinted thereon as evidence of attributes of the article. The indicium including a signature generated with a private key of a first party; a certificate; information specifying attributes of the article. The private key of the first party is generated as a function of the certificate, the information, and a private key of a certifying authority, the function being chosen so that a party wishing to verify the indicium can determine a public key corresponding to the private key of the first party by operating on the certificate and the information with a corresponding public key of the certifying authority.

10

A digital postage meter in accordance with the subject invention is controlled to print indicia signed with a private key Key_{DM} based upon a published finite group $[P]$ with a binary operation $[+]$ and a published particular point P in the group and a published binary operation $K * P$, where K is an integer and P is a point in the group, such that $K * P$ is a point in the group computed by applying the operation $[+]$ to K copies of the point P , and computation of K from knowledge of the definition of the group $[P]$, the point P , and $K * P$ is hard, so that a public key $Key_{DM} * P$ of the digital postage meter can be determined by a party seeking to verify indicia printed by the digital postage meter from published information with assurance that the public key $Key_{DM} * P$ has been certified by a certifying authority CA. The meter is controlled to; generate a random number r_{DM} and send a point $r_{DM} * P$ to a certifying station; receive a certificate $CERT_{DM}$ from a certifying station operated by the certifying authority CA, wherein;

20

$$CERT_{DM} = (r_{DM} + r_{CA}) * P; \text{ and wherein}$$

r_{DM} is a random integer generated by the digital postage meter and r_{CA} is a random integer generated by the certifying station; receive an integer I_{DM} from the certifying station, wherein;

25

$$I_{DM} = r_{CA} + H(M)Key_{CA}; \text{ and wherein}$$

M is a message published by the certifying station and $H(M)$ is an integer derived from the message M in accordance with a publicly known algorithm H and Key_{CA} is a private key of the certifying authority CA; compute a private key Key_{DM} ,

30

$$\text{Key}_{\text{DM}} = r_{\text{DM}} + I_{\text{DM}} = r_{\text{DM}} + r_{\text{CA}} + H(M)\text{Key}_{\text{CA}};$$

and print an indicium and digitally sign the indicium with the key Key_{DM} .

A certifying station operated by a certifying authority CA in accordance with the subject invention is controlled to publish information relating to a digital postage meter for printing indicia signed with a private key Key_{DM} based upon a published a finite group [P] with a binary operation [+] and a published particular point P in the group and a published a binary operation $K * P$, where K is an integer and P is a point in the group, such that $K * P$ is a point in the group computed by applying the operation [+] to K copies of the point P, and computation of K from knowledge of the definition of the group [P], the point P, and $K * P$ is hard, so that a public key $\text{Key}_{\text{DM}} * P$ of the digital postage meter can be determined by a party seeking to verify indicia printed by the digital postage meter from the published information with assurance that the public key $\text{Key}_{\text{DM}} * P$ has been certified by a certifying authority CA. The station is controlled to; receive a point $r_{\text{DM}} * P$ from the digital postage meter, where r_{DM} is a random number generated by the digital postage meter; generate and send to the digital postage meter a certificate CERT_{DM} , wherein;

$$\text{CERT}_{\text{DM}} = (r_{\text{DM}} + r_{\text{CA}}) * P; \text{ and wherein}$$

r_{CA} is a random integer generated by the certifying station; generate and send to the digital postage meter an integer I_{DM} , wherein;

$$I_{\text{DM}} = r_{\text{CA}} + H(M)\text{Key}_{\text{CA}}; \text{ and wherein}$$

M is a message published by the certifying station and $H(M)$ is an integer derived from the message M in accordance with a publicly known algorithm H and Key_{CA} is a private key of the certifying authority CA

In accordance with still another aspect of the subject invention a certifying authority certifies a public key of a digital postage meter, the digital postage meter producing indicia signed with a corresponding private key of the digital postage meter, the certifying authority having a published public key and a corresponding private key, by providing the meter with an integer, the integer being a first function of the private key

of the authority; the meter computing a digital postage meter private key as a second function of the integer; and the certifying authority publishing related information. The first function, the second function and the published related information are chosen so that a party seeking to verify the indicia can compute the digital postage meter public key by operating on the published related information with the published public key of the authority.

In accordance with still another aspect of the subject invention a certifying authority certifies a public key of a digital postage meter, the digital postage meter producing indicia signed with a corresponding private key of the digital postage meter, the certifying authority having a published public key and a corresponding private key, by the certifying authority providing a user with an integer, the integer being a first function of the private key of the authority; the user computing a digital postage meter private key as a second function of the integer and downloading the postage meter private key to the digital postage meter ; and the certifying authority publishing related information. The first function, the second function and the published related information are chosen so that a party seeking to verify the indicia can compute the digital postage meter public key by operating on the published related information with the published public key of the authority.

Other objects, advantages and features of the subject invention will be apparent from consideration of the attached drawings and the detailed description set forth below.

Brief Description of the Drawings

Figure 1 is a graph illustrating the prior art operation of point addition of points P and P'.

Figure 2 is a graph illustrating the prior art operation of point addition of two copies of point P.

Figure 3 is a graph illustrating the prior art operation of point multiplication of point P.

Figure 4 is a schematic block diagram of a general encryption station which can be programmed to serve in digital postage meters, user stations or certifying stations.

Figures 5 and 6 show communication of a digital postage meter and a certifying station over a data link to generate a public key pair and certificate in accordance with the method of the subject invention.

Figures 7 and 8 show communication of a user station and a certifying station over a data link to generate a public key pair for downloading to a digital postage meter, and a certificate in accordance with the method of the subject invention.

Figure 9 is a schematic representation of a digital indicium in accordance with the subject invention.

Detailed Description of Preferred Embodiments of the Invention

Figure 4 shows a general encryption station 20 which can be adapted to perform the functions required by a user or a certifying authority. Station 20 can also be incorporated into a digital postage meter in embodiments of the subject invention where a communications link is provided between a certifying authority and a postage meter for generation of public key pairs and corresponding certificates.

Digital postage meters are well known devices for printing mail pieces with indicia evidencing payment of postage and accounting for postage expended and a description of their operation in carrying out these functions is not necessary for an understanding of the subject invention. Also, it will be apparent to those skilled in the art

that the various functional units shown in Figure 4 need not be incorporated in corresponding hardware subsystems but can be provided, wholly or partially, by appropriate software routines.

Station 20 includes processor 22 connected to data link 24 through I/O device 26. Data link 24 may be of any convenient kind, including but not limited to computer communication networks, telephone networks and dedicated lines, or can simply be the exchange of portable data storage media such as magnetic disks, with I/O device 26 being designed in a conventional manner to interface to link 24.

Processor 22 also communicates with program memory 32 to access program code to control station 20 to carry out functions of a user or digital postage meter in generating a public key pair, or of certifying authority in generating a corresponding certificate, and working memory 34 for temporary storage of data.

To increase security, station 20 also includes secure memory 35 for storing certain critical parameters, as will be described further below. Preferably memory 35 is secured against unauthorized access by conventional means known to those skilled in the art, which can include physical security such as shielding and software based techniques such as passwords and encryption.

Processor 22 also communicates with, and controls as necessary: encryption engine 38 for carrying out point additions and point multiplications; hash engine 40 for performing a publicly known hash function, preferably the SHA-1 hash function promulgated by the National Security Agency; and random number generator 42 for generating random numbers. While the above described engines have been shown as dedicated devices for clarity of illustration, in other embodiments the encryption, hashing, and random number generation functions can be carried out by software routines stored in program memory 32.

Station 20 is preferably adapted to carry out the functions of a user or a certifying authority by reading signals representative of an appropriate control program code recorded on portable media such as magnetic disks 46U or 46CA into program memory through disk drive 48 (For security reasons postage meters are preferably not designed to be programmable. Details of the operations of certifying authorities and users, or digital postage meters, in carrying out the method of the subject invention are described more fully below and development of control programs to control stations to function in such roles would be well within the ability of a person skilled in the cryptographic art.).

Figures 5 and 6 show a digital postage meter and a certifying station having substantially the architecture shown in Figure 4 which communicate over data link 24 to carry out the method of the subject invention in an embodiment where digital postage meters communicate directly with a certifying authority. Public data store 46 is also connected to link 24 to store data accessible to any party communicating over link 24.

Initially meter 20DM stores identifying information ID_{DM} (e.g. a meter identification number), a description of a group $[P]$ (i.e. information needed to carry out additive operation $[+]$) and a particular, publicly known point P in its working memory 34DM, and stores a previous private Key_p in secure memory 35DM. A certifying station 20CA operated by a certifying authority (which can be a postal authority or an agent such as an equipment supplier designated by a postal authority), stores $[P]$, P , and information $I_{AV_{DM}}$ which identifies or characterizes meter 20 DM, as will be described further below, in its working memory 34CA; and private key Key_{CA} in secure memory 35CA.; and public data store 46 stores public key $Key_{CA} * P$.

Meter 20DM initiates the certification process by generating and storing a random number r_{DM} in secure memory 35DM, computing the point $r_{DM} * P$, and sending point $r_{DM} * P$ to station 20CA together with its identifying information ID_{DM} . The information is signed using the previous private key of meter 20DM to provide assurance to station 20CA as to the source of the information. An initial private key can be installed in meter

20DM by the equipment supplier. Other methods for assuring the source of communications, such as physical control of the device, secure channels or call back protocols can also be used to provide assurance of the source of the information.

- 5 In Figure 6 station 20CA identifies the Identity and Attributes Value for meter 20DM IAV_{DM} and then generates and stores a random number r_{CA} in secure memory 35CA and computes the point:

$$OMC_{DM} = r_{DM} * P \quad [+] \quad r_{CA} * P = (r_{DM} + r_{CA}) * P$$

- 10 In the case where a certifying station cannot certify meter 20DM the station can enter an error routine to abort the certification process. Details of such an error routine form no part of the subject invention. In other embodiments of the invention, successive certifying stations can alter or amend information ID_U to indicate user U's status.

- 15 Station 20CAF then generates message M:

$$M = OMC_{DM}, IAV_{DM}$$

and computes a hash $H(M)$ of message M where H is a publicly known hashing function and is preferably the known SHA-1 function and then generates an integer I_{DM} :

$$I_{DM} = r_{CA} + H(M)Key_{CA}$$

- 20 and sends integer I_{DM} to meter 20DM together with OMC_{DM} and IAV_{DM} . (In computing integer I_{DM} the expression of point OMC_{DM} is handled as an integer.)

Meter 20DM then computes private key Key_U :

- 25 $Key_{DM} = r_{DM} + I_{DM} = r_{DM} + r_{CA} + H(M)Key_{CA}$

Meter 20DM then uses Key_{DM} to sign indicia it generates, as will be described further below. A postal authority or other party seeking to verify meter 20DM's public key can compute $Key_{DM} * P$ as:

- 30 $Key_{DM} * P = OMC_{DM} [+] H(M) Key_{CA} * P =$

$$r_{DM} + r_{CA} * P + H(M)Key_{CA} * P$$

from knowledge of H, M, said public key $Key_{CA} * P$, and OMC_{DM} . Since the computation of public key $Key_{DM} * P$ requires public key $Key_{CA} * P$ the verifying party has assurance that $Key_{DM} * P$ has been certified by certifying authority CA.

5

Figures 7 and 8 show a user and a certifying station having substantially the architecture shown in Figure 4 which communicate over data link 24 to carry out the method of the subject invention in an embodiment where a user, which can be a digital postage meter supplier communicates with a certifying authority to obtain public key pairs and download the private keys to digital postage meters. This embodiment is

10 believed to be advantageous since, assuming trust of the user by the certifying authority, the substantial expense and complexity of maintaining a communications infrastructure with large numbers of digital postage meters is avoided. Public data store 46 is also connected to link 24 to store data accessible to any party communicating over link 24.

15

Initially user station 20U stores identifying information ID_{50} for digital postage meter 50 (e.g. a meter identification number), a description of a group [P] (i.e. information needed to carry out additive operation [+]) and a particular, publicly known point P in its working memory 34U, and stores user private Key_U in secure memory 35U.

20 Certifying station 20CA stores [P], P, and information IAV_{50} which identifies or characterizes meter 50 in its working memory 34CA; and private key Key_{CA} in secure memory 35CA.; and public data store 46 stores public key $Key_{CA} * P$.

20

User station 20U initiates the certification process by generating and storing a

25 random number r_{50} in secure memory 35U, computing the point $r_{50} * P$, and sending point $r_{50} * P$ to station 20CA together with its identifying information ID_{50} . The information is signed using the private key of station 20U to provide assurance to station 20CA as to the source of the information. Other methods for assuring the source of communications, such as secure channels or call back protocols can also be used to provide assurance of

30 the source of the information.

In Figure 6 station 20CA identifies the Identity and Attributes Value for meter 50 IAV₅₀ and then generates and stores a random number r_{CA} in secure memory 35CA and computes the point:

$$5 \quad \text{OMC}_{50} = r_{50} * P \quad [+] \quad r_{CA} * P = (r_{50} + r_{CA}) * P$$

In the case where a certifying station cannot certify meter 50 the station can enter an error routine to abort the certification process. Details of such an error routine form no part of the subject invention.

10

Station 20CAF then generates message M:

$$M = \text{OMC}_{50}, \text{IAV}_{50}$$

and computes a hash H(M) of message M where H is a publicly known hashing function and is preferably the known SHA-1 function and then generates an integer I₅₀:

$$15 \quad I_{50} = r_{CA} + H(M) \text{Key}_{CA}$$

and sends integer I₅₀ to station 20U, together with OMC₅₀ and IAV₅₀.

Station 20U then computes private key Key₅₀:

$$20 \quad \text{Key}_{50} = r_{50} + I_{DM} = r_{50} + r_{CA} + H(M) \text{Key}_{CA};$$

and downloads Key₅₀, together with OMC₅₀ and IAV₅₀, to meter 50.

Meter 50 then uses Key₅₀ to sign indicia it generates, as will be described further below. A postal authority or other party seeking to verify meter 50's public key can

25 compute Key₅₀*P as:

$$\begin{aligned} \text{Key}_{50} * P &= \text{OMC}_{50} [+] H(M) \text{Key}_{CA} * P = \\ & (r_{50} + r_{CA}) * P + H(M) \text{Key}_{CA} * P \end{aligned}$$

from knowledge of H, M, said public key Key_{CA}*P, and OMC₅₀. Since the computation of public key Key_{DM}*P requires public key Key_{CA}*P the verifying party has
30 assurance that Key₅₀*P has been certified by certifying authority CA.

While in the embodiment shown in Figures 7 and 8 only a single meter is described for reasons of clarity, those skilled in the art will recognize that this embodiment is particularly advantageous for the generation of blocks of public key pairs and corresponding certificates.

Further, while Key_{50} is shown as being downloaded over data link 24 and encrypted with user's key Key_U for security, in other embodiments the user may physically load keys into meters prior to delivery to mailers. Also, suppliers may operate certifying stations in the manner described with respect to Figures 5 and 6 to provide new keys to meters, for example after remote or physical inspection of meters; and suppliers can obtain initial keys Key_p , described with respect to Figures 5 and 6, in the manner shown in Figures 7 and 8.

Turning to Figure 9, a postal indicia in accordance with the subject invention is shown.

(Though the following description is set forth with respect to meter 20DM those skilled in the art will understand that it applies equally to meter 50 and other meters in accordance with the subject invention, since the operations of generating and signing postal indicia and verifying public keys used to sign such indicia are substantially identical without regard to particular sequences of operations used to generate public key pairs and certificates.)

In Figure 9 indicium 60 includes human readable parameters 62 (which can be OCR scanable), scanable mailpiece parameters 64, Identification and Attribute Value 66, Optimal Mail Certificate 70, and digital signature 72.

Human readable parameters include postage value 74, date 78 and other desired parameters 80 which are provided for the convenience of postal personnel and for the

detection of mail underrating and the like. These parameters do not form part of the subject invention per se.

Scanable mail piece parameters are printed in a machine readable form such as the commercially available 2-dimensional barcodes “DataMatrix” and “Aztec” or the stacked barcode PDF417. Scanable mail piece parameters can include parameters such as meter accounting register values, meter sequential counter values, mail piece rating parameters such as weight or size, delivery control code, e.g. destination zipcode, and can also include values which are included in human readable parameters 62. These values can form part of the signed portion of indicium 60 if assurance as to their correctness is desired, or can be used only to facilitate handling of the mailpiece.

IAV 66 is also represented in machine readable form and, as described above, forms part of the signed portion of the indicia and includes meter identification 82, expiration date of the certificate 86, maximum postage value 90, and other parameters 92 such as a range of allowable postal codes, date of last meter inspection, or values of meter security sensors. Since the public key pair and corresponding OMC are functions of IAV it is preferred that IAV values remain constant for processing of a substantial number of mailpieces, preferably 10,000 or more; however if communications and processing rates are high enough IAV values can vary more rapidly.

OMC 70 also forms part of the signed portion of indicium 60.

Digital signature 72 (i.e. the CIVC) can be generated using known techniques and a more detailed description of signature mechanisms is not required for an understanding of the subject invention.

In particular embodiments CIVC values can be generated in one of two general ways: a digital signature with appendix, or a digital signature with message recovery. (See Handbook of Applied Cryptography A. Menezes, P. Van Oorshot, and S. Vanstone

CRC Press 1997) Use of signatures with appendix is well known and involves generating a hash of the message to be signed, using a known hash function, and encrypting the hash. In public key systems the recipient also generates a hash of the message and compares it to the decrypted hash received with the message. Successful comparison validates the signature, i.e. signature of the message. Typical such algorithms are the RSA, DSA, and ECDSA algorithms and signing with appendix, (e.g. ECDSA) can be used with the subject invention.

In other preferred embodiments digital signature with message recovery can be used. Signatures with message recovery rely upon encryption of all or a portion of a message which is successfully recovered from the signature or CIBC and validated by internal redundancies; i.e. there is sufficient internal redundancy in the message that it is highly unlikely that a falsely signed message will not be internally inconsistent when recovered. These techniques for signing are particularly useful for signing of short messages and are preferred for signing of postal indicia which are necessarily short due to the size limitations discussed above and which include a high degree of redundancy.

To sign a postal indicium in accordance with these embodiments a postage meter or mailing system defines a message m including indicia data requiring protection such as postage value, date, ascending register value, piece count and perhaps other data need to provide increased redundancy. Preferably m is less than approximately 20 bytes. (The signing method of this embodiment will work with larger messages but is believed less effective.) A meter or mailing system processor, which is preferably a secure co-processor or cryptoprocessor, generates a random integer r_s , $r_s < n$ where n is the order of $[P]$ and computes the integer $K = K(r_s * P)$ where K is any convenient mapping of a point in $[P]$ onto the integers. The processor then generates e with a known symmetric key encryption algorithm using key K (hereinafter SKE_K) where:

$$e = SKE_K(m)$$

The processor then computes $H(e, IAV)$ where H is again preferably the SHA1 hashing function and computes:

$$s = \text{Key}_M H(e, IAV) + r_s$$

where Key_M is the private key of the meter or mailing system.

5

The signature for message m is the pair (s, e)

A postal authority or other party wishing to verify an indicium derives the meter public key $\text{Key}_M * P$ as described above and computes:

10

$$\begin{aligned} s * P [-] H(e, IAV) \text{Key}_M * P &= \\ H(e, IAV) \text{Key}_M * P [+] r_s * P [-] H(e, IAV) \text{Key}_M * P &= \\ r_s * P \end{aligned}$$

from values of e , IAV and Key_M recovered from the indicium and knowledge of H , and then recovers:

15

$$\begin{aligned} K &= K(r_s * P) \\ m &= \text{SKE}_K^{-1}(e) \end{aligned}$$

where SKE_K^{-1} is the inverse of SKE_K , and accepts m as valid if it is internally consistent. ($[-]$ is "point subtraction, the inverse of $[+]$ and its meaning will be apparent from inspection of Figure 1.)

20

This method has particular advantages for postal indicia since plain text of m need not be incorporated into the indicia, saving scarce space in the indicia while protecting critical values.

25

It will be apparent to those skilled in the art that OMC and IAV need not be signed in this embodiment since they are necessary to derive $\text{Key}_M * P$ and so are self-validating.

30

Public key $\text{Key}_{CA} * P$ can also be included in indicium 60 to facilitate verification with out the need to communicate with an external data base, space permitting. However

key $\text{Key}_{\text{CA}}^*P$ is also published, as for example by storage in public data store 46, to allow at least periodic independent verification.

Certificates generally are controlled by a validity period and authenticate that the certificate owner has certain rights. By incorporating limiting parameters such as expiration date or maximum postage value into the certificate as described above a simple check of the parameters enables the verification authority to detect mail pieces produced by a digital postage meter with an expired certificate or which otherwise exceeds parameter limits. This equivalent to revocation of the certificate but simpler and more automatic in execution and provide a finer control of the system.

In other embodiments of the subject invention certification can be carried out, substantially as described above, over other sets $[E]$ for which an operation $[op]$ exists such that $I[op]E$, where I is an integer, is an element of $[E]$ and computation of I from knowledge of $[E]$, E , and $I[op]E$ is hard. For example the Digital Signature Algorithm is based on a subgroup of integers modulo a prime number p with binary operation being exponentiation. However, elliptic curves are preferred as computationally more efficient.

The embodiments described above and illustrated in the attached drawings have been given by way of example and illustration only. From the teachings of the present application those skilled in the art will readily recognize numerous other embodiments in accordance with the subject invention. In particular they will recognize that numerous other arrangements for the generation of public key pairs and corresponding certificates, depending upon the trust model assumed to apply among the parties, will be apparent to those skilled in the art from the above descriptions and are within the contemplation of the subject invention. Accordingly, limitations on the subject invention are to be found only in the claims set forth below.

What is claimed is:

1. A method for controlling, and distributing information between a digital postage meter and a certifying station operated by a certifying authority CA for publishing information, so that a public key $\text{Key}_{\text{DM}}^*P$ of said digital postage meter can be determined by a party seeking to verify indicia printed by said digital postage meter from said published information with assurance that said public key $\text{Key}_{\text{DM}}^*P$ has been certified by said certifying authority CA, said method comprising the steps of:

a) defining and publishing a finite group [P] with a binary operation [+]
and publishing a particular point P in said group;

b) defining and publishing a binary operation $K * P$, where K is an integer and P is a point in said group, such that $K * P$ is a point in said group computed by applying said operation $[+]$ to K copies of said point P , and computation of K from knowledge of the definition of said group $[P]$, said point P , and $K * P$ is hard;

c) controlling a certifying station to publish a certificate CERT_{DM} for said digital postage meter, wherein;

$CERT_{DM} = (r_{DM} + r_{CA}) * P$; and wherein

r_{DM} is a random integer generated by said digital postage meter and r_{CA} is a random integer generated by said certifying station;

d) controlling said certifying station to publish a message M;

e) controlling said certifying station to generate an integer I_{DM} , and send said integer to said digital postage meter, wherein;

$$I_{DM} = r_{CA} + H(M)Key_{CA}; \text{ and wherein}$$

$H(M)$ is an integer derived from said message M in accordance with a publicly known algorithm H and Key_{CA} is a private key of said certifying authority CA ;

f) publishing a public key $\text{Key}_{\text{CA}}^*P$ for said certifying authority CA; and

g) controlling said digital postage meter to compute a private key Key_{DM} ,

$$\text{Key}_{\text{DM}} = r_{\text{DM}} + I_{\text{DM}} = r_{\text{DM}} + r_{\text{CA}} + H(M)\text{Key}_{\text{CA}}; \text{ and}$$

h) controlling said digital postage meter to print an indicium and digitally sign said indicium with said key Key_{DM} ; whereby

i) said verifying party can compute said user's public key $\text{Key}_{\text{DM}}^*P$ as

$$\begin{aligned} \text{Key}_{\text{DM}}^*P &= \text{CERT}_{\text{DM}} + H(M) \text{Key}_{\text{CA}}^*P = \\ &= (r_{\text{DM}} + r_{\text{CA}})^*P + H(M)\text{Key}_{\text{CA}}^*P \end{aligned}$$

from knowledge of H, M, [P], said public key $\text{Key}_{\text{CA}}^*P$, and CERT_{DM} .

2. A method as described in claim 1 wherein said publicly known manner for deriving an integer from said published information comprises applying a hashing function to said message M.

3. A method as described in claim 2 wherein said message M includes information IAV identifying said digital postage meter and operating parameters applicable to said digital postage meter.

4. A method as described in claim 2 wherein said message M includes information IAV identifying said digital postage meter and operating parameters applicable to said digital postage meter.

5. A method as described in claim 1 wherein said group [P] is defined on an elliptic curve.

6. A method as described in claim 1 wherein said message M includes information tying said user's public key $\text{Key}_U * P$ to said information IAV.

7. A article having an indicium imprinted thereon as evidence of attributes of said article, said indicium comprising:

a) a signature generated with a private key of a first party;

b) a certificate;

c) information specifying attributes of said article; wherein

d) said private key of said first party is generated as a function of said certificate, said information, and a private key of a certifying authority, said function being chosen so that a party wishing to verify said indicium can determine a public key corresponding to said private key of said first party by operating on said certificate and said information with a corresponding public key of said certifying authority.

8. A method for controlling a digital postage meter to print indicia signed with a private key Key_{DM} based upon a published a finite group [P] with a binary operation [+] and a published particular point P in said group and a published a binary operation $K * P$, where K is an integer and P is a point in said group, such that $K * P$ is a point in said group computed by applying said operation [+] to K copies of said point P, and computation of K from knowledge of the definition of said group [P], said point P,

and $K \cdot P$ is hard, so that a public key $\text{Key}_{\text{DM}} \cdot P$ of said digital postage meter can be determined by a party seeking to verify indicia printed by said digital postage meter from published information with assurance that said public key $\text{Key}_{\text{DM}} \cdot P$ has been certified by a certifying authority CA, said method comprising the steps of:

a) controlling said digital postage meter to generate a random number r_{DM} and send a point $r_{\text{DM}} \cdot P$ to a certifying station;

b) controlling said digital postage meter to receive a certificate CERT_{DM} from a certifying station operated by said certifying authority CA, wherein;

$$\text{CERT}_{\text{DM}} = (r_{\text{DM}} + r_{\text{CA}}) \cdot P; \text{ and wherein}$$

r_{DM} is a random integer generated by said digital postage meter and r_{CA} is a random integer generated by said certifying station;

c) controlling said digital postage meter to receive an integer I_{DM} from said certifying station, wherein;

$$I_{\text{DM}} = r_{\text{CA}} + H(M) \text{Key}_{\text{CA}}; \text{ and wherein}$$

M is a message published by said certifying station and $H(M)$ is an integer derived from said message M in accordance with a publicly known algorithm H and Key_{CA} is a private key of said certifying authority CA;

d) controlling said digital postage meter to compute a private key Key_{DM} ,

$$\text{Key}_{\text{DM}} = r_{\text{DM}} + I_{\text{DM}} = r_{\text{DM}} + r_{\text{CA}} + H(M) \text{Key}_{\text{CA}}; \text{ and}$$

e) controlling said digital postage meter to print an indicium and digitally sign said indicium with said key Key_{DM} ; whereby

f) said verifying party can compute said digital postage meter public key $\text{Key}_{\text{DM}} \cdot P$ as

$$\text{Key}_{\text{DM}} \cdot P = \text{CERT}_{\text{DM}} + H(M) \text{Key}_{\text{CA}} \cdot P =$$

$$(r_{DM} + r_{CA}) * P + H(M)Key_{CA} * P$$

from knowledge of H, M, [P], said public key $Key_{CA} * P$, and $CERT_{DM}$.

9. A method for controlling a certifying station operated by a certifying authority CA to publish information relating to a digital postage meter for printing indicia signed with a private key Key_{DM} based upon a published a finite group [P] with a binary operation [+] and a published particular point P in said group and a published a binary operation $K * P$, where K is an integer and P is a point in said group, such that $K * P$ is a point in said group computed by applying said operation [+] to K copies of said point P, and computation of K from knowledge of the definition of said group [P], said point P, and $K * P$ is hard, so that a public key $Key_{DM} * P$ of said digital postage meter can be determined by a party seeking to verify indicia printed by said digital postage meter from said published information with assurance that said public key $Key_{DM} * P$ has been certified by a certifying authority CA, said method comprising the steps of:

a) controlling said certifying station to receive a point $r_{DM} * P$ from said digital postage meter, where r_{DM} is a random number generated by said digital postage meter;

b) controlling said certifying station to generate and send to said digital postage meter a certificate $CERT_{DM}$, wherein;

$$CERT_{DM} = (r_{DM} + r_{CA}) * P; \text{ and wherein}$$

r_{CA} is a random integer generated by said certifying station;

c) controlling said certifying station to generate and send to said digital postage meter an integer I_{DM} , wherein;

$$I_{DM} = r_{CA} + H(M)Key_{CA}; \text{ and wherein}$$

M is a message published by said certifying station and H(M) is an integer derived from said message M in accordance with a publicly known algorithm H and Key_{CA} is a private key of said certifying authority CA; whereby

d) said digital postage meter can compute said private key Key_{DM},

$$\text{Key}_{\text{DM}} = r_{\text{DM}} + I_{\text{DM}} = r_{\text{DM}} + r_{\text{CA}} + H(M)\text{Key}_{\text{CA}}; \text{ and}$$

and digitally sign said indicium with said key Key_{DM}; and whereby

e) said verifying party can compute said digital postage meter public key Key_{DM}*P as

$$\text{Key}_{\text{DM}}*P = \text{CERT}_{\text{DM}} + H(M) \text{Key}_{\text{CA}}*P =$$

$$(r_{\text{DM}} + r_{\text{CA}})*P + H(M)\text{Key}_{\text{CA}}*P$$

from knowledge of H, M, [P], said public key Key_{CA}*P, and CERT_{DM}.

10. A method for certification by a certifying authority of a public key of a digital postage meter, said digital postage meter producing indicia signed with a corresponding private key of said digital postage meter, said certifying authority having a published public key and a corresponding private key, said method comprising the steps of:

a) said certifying authority providing said meter with an integer, said integer being a first function of said private key of said authority;

b) said meter computing a digital postage meter private key as a second function of said integer; and

c) said certifying authority publishing related information; wherein

d) said first function, said second function and said published related information are chosen so that a party seeking to verify said indicia can compute said digital postage meter public key by operating on said published related information with said published public key of said authority.

11. A method as described in claim 10 wherein said published related information includes information identifying said digital postage meter and operating parameters applicable to said digital postage meter.

12. A method for certification by a certifying authority of a public key of a digital postage meter, said digital postage meter producing indicia signed with a corresponding private key of said digital postage meter, said certifying authority having a published public key and a corresponding private key, said method comprising the steps of:

a) said certifying authority providing a user with an integer, said integer being a first function of said private key of said authority;

b) said user computing a digital postage meter private key as a second function of said integer and downloading said postage meter private key to said digital postage meter; and

c) said certifying authority publishing related information; wherein


d) said first function, said second function and said published related information are chosen so that a party seeking to verify said indicia can compute said digital postage meter public key by operating on said published related information with said published public key of said authority.

13. A method as described in claim 12 wherein said published related information includes information identifying said digital postage meter and operating parameters applicable to said digital postage meter.

Abstract of the Disclosure

- 5 A method for certifying the public key of a digital postage meter using a public key encryption system by a certifying authority. A certifying station and a user station, or a digital postage meter, exchange information and the user station and downloads, or the meter derives, a public key from the exchanged information. The certifying station also publishes related information and its public key. A third party can derive the public key
- 10 corresponding to the meter's private key by operating on the published information with the certifying station public key.

1/9

[illegible]



$\frac{2}{9}$ 

FIG. 2
PRIOR ART

[illegible]



00000000 00000000







FIG. 4

4/9
E-831




00000000.00000000



24




T_{DM} * P, ID_{DM}, SIGN(KEY_P)



E-631
5/9

PUBLIC DATA STORAGE	46
KEY _{CA} * P	



DIGITAL POSTAGE METER	20DM
WORKING MEMORY	ID _{DM} , [P], P, OMC _{DM}
	IAV _{DM} , KEY _{CA} * P
	34DM
SECURE MEMORY	KEY _P → KEY _{DM} = I _{DM} + r _{DM}
	35DM

CERTIFYING STATION	20CA
WORKING MEMORY	OMC _{DM} = (T _{DM} + E _{CA}) * P
	M = OMC _{DM} - IAV _{DM}
	I _{DM} = H(M) + r _{CA}
	34CA
SECURE MEMORY	KEY _{CA}
	r _{CA}
	35CA


E-831

4/9

FILE 6666.033099

E-831

7/9



09276.728.032099

E-831
9/9





Figure 8-22-033099



DECLARATION AND POWER OF ATTORNEY
Patent Application

Attorney's Docket Number
E-831

Page 1 of 3

As below named inventors, we hereby declare that:

our residences, post office addresses and citizenships are as stated below next to our names;

we believe that we are the original, first and joint inventors of the subject matter which is claimed and for which a patent is sought on the invention entitled

**METHOD FOR CERTIFYING PUBLIC KEYS USED TO SIGN POSTAL
INDICIA AND INDICIA SO SIGNED**

described and claimed in the attached specification;

we have reviewed and understand the contents of the above-identified specification, including the claims;

we acknowledge our duty to disclose to the Patent and Trademark Office all information known to us to be material to the patentability of this application as defined in Title 37, Code of Federal Regulations, section 1.56; and

we do not know and do not believe the invention was ever known or used in the United States of America before our invention thereof, or patented or described in any printed publication in any country before our invention thereof or more than one year prior to this application, that the invention was not in public use or on sale in the United States of America more than one year prior to this application, that the invention has not been patented or made the subject of an inventor's certificate issued before the date of this application in any country foreign to the United States of America on any application filed by us or our legal representatives or assigns more than twelve months prior to this application, and that no application for patent or inventor's certificate on this invention has been filed in any country foreign to the United States of America prior to this application by us or our legal representatives or assigns.

We hereby appoint the following attorneys and/or agents to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith;

Charles R. Malandra, Jr.
Melvin J. Scolnick
David E. Pitchenik
Robert E. Meyer

Reg. No. 31,038
Reg. No. 25,233
Reg. No. 24,020
Reg. No. 26,307

DECLARATION AND POWER OF ATTORNEY

Patent Application

Attorney's Docket Number

E-831

Page 2 of 3

Address all telephone calls to Charles R. Malandra, Jr.
at telephone No.: (203) 924-3217.

Address all correspondence to:

Charles R. Malandra, Jr.
Pitney Bowes Inc.
Intellectual Property and
Technology Law Department
35 Waterview Drive
P.O. Box 3000
Shelton, CT 06484

We hereby declare that all statements made herein of our own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Full Name	Last CORDERY	First ROBERT	Middle A	
Residence & Citizenship	City DANBURY	State CT	Citizenship USA	
Post Office Address	Street Address 11 1/2 Jeanette Street	City Danbury	State CT	Zip Code 06811
Signature of Inventor			Date	

FULL NAME	Last PINTSOV	First LEON	Middle	
Residence & Citizenship	City	State	Citizenship	
Post Office Address	Street Address	City	State	Zip Code
Signature of Inventor			Date	

DECLARATION AND POWER OF ATTORNEY Patent Application			Attorney's Docket Number E-831	
			Page 3 of 3	
FULL NAME	Last VANSTONE	First SCOTT		Middle
Residence & Citizenship	City		State	Citizenship
Post Office Address	Street Address	City	State	Zip Code
Signature of Inventor				Date